



More than products. A partnership.

MKN

Professional road cleaning brush

MKN is a brush for street and road cleaning. It can be equipped with a tank for collecting dust and small debris.



✓ Cleaning efficiency

The brush completely adapts to the surface being cleaned, using an axial tilt system. Auxiliary wheels ensure even brush pressure on the surface, enabling thorough cleaning.

✓ Maintenance after the winter period

MKN can be equipped with a tank for collecting dust and similar small waste. With cleaning width of 2100 mm, it is ideal for cleaning remaining spreading agent after the winter period.

✓ Mounting on tractor, Unimog or construction vehicle

MKN can be mounted on tractor front mounting plate or front hydraulic levers, on a Unimog or on construction vehicle via special type of mounting plate.



BASIC PARTS



1 | Front brush

Cleans up to 2100 mm wide. Ideal for cleaning roads and road edges from residual spreading agent after winter period.

4 | Water spraying system

To prevent dust from rising during work, the MKN can be equipped with a water spraying system with nozzles. In this case, 12L / min water pumps are installed on the brush.

7 | Control

The MKN brush is controlled via diverter or via hydraulic control unit built into the vehicle cab.

2 | Side brush

It is used for thorough cleaning of road areas where large brush can't reach.

5 | Water tank

Water tank with 200 or 350 L volume is mounted above the brush housing. A tank with a 1000 or 2000 L volume is mounted in the tipper box, or on the rear levers of the carrying vehicle.

3 | Dust tank

Used to collect dust, gravel and small debris. It is easily emptied and maintained.

6 | Mounting system

MKN can be mounted on the front side of Unimog vehicle, on front plate or front hydraulic levers of the tractor, or on a front mounting plate on construction vehicle.

TECHNICAL CHARACTERISTICS

Cleaning width	Total width	Brush diameter
	mm	
2100	2380	600 / 178

CHOICE OF EQUIPMENT

- Side brush with hydraulic motor
- Dust tank with an emptying cylinder
- Preparation for road washing with nozzles
- Water pump 12 L / min
- 200 or 300 L water tank, mounted above the housing
- 1000 or 2000 L water tank, mounted in the back of the vehicle
- Mechanical drive of horizontal brush
- Driving cardan shaft
- Electrohydraulic control with a control unit in the vehicle cab
- Control by diverter
- Three-way flow regulator
- Different types of mounting plates for various vehicles



RASCO d.o.o.
Kolodvorska 120b
HR - 48361 Kalinovac
CROATIA



+385 48 883 112



rasco@rasco.hr



RascoCompany



Rasco_company



RascoTV



RASCO d.o.o.